

100V Line Speaker Selector Guide

Head Office

Wellington

PO Box 35-063
Naenae
Lower Hutt 5041
17 Eastern Hutt Rd
Wingate
Lower Hutt 5019
Tel (04) 567-3229
Fax (04) 567-3644

www.pertronic.co.nz

sales@pertronic.co.nz
tech@pertronic.co.nz

Auckland Office

PO Box 15-867
New Lynn
Auckland 0640
359 Onehunga Mall
Onehunga
Auckland 1061
Tel (09) 633-0226
Fax (09) 633-0228



ISO 9001: 2008

International
Standards
Certifications
QAC/R64/0012

Products	Dimensions / Fittings	Applications / Colours	Tappings	IP Rating
 PSS1-W PSS1-R	17 x 74 x 12 mm (H x W x D) Flush-box / Surface-mount	Indoor use Colours: White / Red	0.2W / 0.7W / 1.1W	N/A
 PSSB501 PSSB401	122 x 31 mm (Diameter x Height) Surface Mount (PSSB501 includes B501 Addressable Base; PSSB401 includes B401 Conventional Base)	Indoor use Colour: White	0.2W / 0.7W / 1.1W	N/A
 PSS3	136 x 100 mm (Diameter x Height) Flush Mount (Spring-clip)	Indoor use Colour: White (RAL9016)	0.33W / 0.66W / 1.25W / 3W	N/A
 PSS3-LP PSS3-LPSME	136 x 60 mm (Diameter x Height) Flush / Surface Mount (Use with PSS3-LPSME, surface mount only)	Indoor use Colour: White (RAL9016)	0.33W / 0.66W / 1.25W / 3W	N/A
 PSS5	180 x 100 mm (Diameter x Height) Flush Mount (Spring-clip)	Indoor use Colour: White (RAL9016)	0.33W / 0.66W / 1.25W / 2.5W / 5W	N/A
 PSS5-LP PSS5-LPSME	180 x 75 mm (Diameter x Height) Flush / Surface Mount (Use with PSS5-LPSME, surface mount only)	Indoor use Colour: White (RAL9016)	0.33W / 0.66W / 1.25W / 2.5W / 5W	N/A
 PSSHORN	150 x 132 mm (Length x Height) Wall Mount	Indoor use Colour: White	1W / 3W	N/A
 BCS-HS10E	200 x 230 mm (Diameter x Length) Wall Mount	Indoor / Outdoor use Colour: Grey	1.25W / 2.5W / 5W / 7.5W / 10W	IP66
 C2048	185 x 245 mm (Diameter x Length) Wall Mount	Outdoor use Colour: Grey	1.25 W / 2.5 W / 5 W / 7.5 W / 10 W	IP66 Marine Grade

PERTRONIC INDUSTRIES LTD

'Pertronic' and 'Firetronix' are registered trademarks of Pertronic Industries Ltd

